



PRODUCT NEWS

201_28M_TEX

“REMANUFACTURED” DELCO 28MT STARTER MOTORS



TS-1572 *Dry Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113281, 1113282
Applications: Bobcat, MF, NH, Perkins

TS-1580 *Dry Clutch*
12V, CW, 12T-46.5mm Dia.
Replaces: 10479606
Applications: Lister-Petter, Perkins

TS-1624 *Dry Clutch*
24V, CW, 12T-46.5mm Dia.
Replaces: 10479600
Applications: Lister-Petter, Perkins



TS-1574 *Dry Clutch*
12V, CW, 10T-32mm Dia.
Replaces: 1113271, 10461443
Applications: Bobcat, John Deere

TS-1646 *Wet Clutch*
12V, CW, 10T-32mm Dia.
Replaces: 1113283, 10479630
Applications: John Deere

TS-1640 *Wet Clutch*
24V, CW, 10T-32mm Dia.,
Replaces: 1113272
Applications: John Deere



TS-1627 *Wet Clutch*
12V, CW, 12T-46.5mm Dia.
Replaces: 10465348, 10479613
Applications: Bobcat

TS-1641 *Dry Clutch*
24V, CW, 10T-40mm Dia.
Replaces: 10479608, 10479612
Applications: Lister-Petter

TS-1644 *Dry Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 10461463, 10479607
Applications: Lister-Petter, MF, NH



TS-1621 *Wet Clutch*
12V, CW, 10T-32mm Dia.,
3-Term. Solenoid
Replaces: 10465365, 10479624
Applications: CDC, Cummins

TS-1622 *Wet Clutch*
24V, CW, 10T-32mm Dia.,
3-Term. Solenoid
Replaces: 1113291, 10479623
Applications: CDC, Cummins, Mack

TS-1642 *Wet Clutch*
24V, CW, 10T-32mm Dia.,
4-Term. Solenoid
Replaces: 1113294, 10479616
Applications: Champion, Cummins



TS-1573 *Dry Clutch*
12V, CW, 9T-34mm Dia.,
3-Terminal Solenoid
Replaces: 1113286, 10465055
Applications: Agco-Allis, Gleaner

TS-1647 *Dry Clutch*
12V, CW, 9T-34mm Dia.,
4-Terminal Solenoid
Replaces: 10461467, 10479620
Applications: Agco-Allis



TS-1575 *Dry Clutch*
12V, CW, 12T-46.5mm Dia.
Replaces: 1113273, 10465058
Applications: Bobcat, Hyster, Perkins

TS-1576 *Dry Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113274, 10465044
Applications: MF, NH, Perkins

TS-1618 *Wet Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113290, 10461485
Applications: Hyster, Perkins

TS-1620 *Dry Clutch*
12V, CW, 10T-32mm Dia.
Replaces: 10461460, 10479604
Applications: Cummins, Oshkosh



TS-1578 *Dry Clutch*
12V, CW, 10T-32mm Dia.,
3-Terminal Solenoid
Replaces: 1113276, 10479621
Applications: Cummins, Freightliner

TS-1579 *Dry Clutch*
12V, CW, 10T-40mm Dia.,
3-Terminal Solenoid
Replaces: 1113275, 1113278
Applications: Hyster, Perkins

TS-1602 *Dry Clutch*
24V, CW, 10T-32mm Dia.,
3-Terminal Solenoid
Replaces: 1113277, 10461468
Applications: Cummins, Timberjack

TS-1619 *Dry Clutch*
24V, CW, 10T-40mm Dia.,
3-Terminal Solenoid
Replaces: 10461461, 10479605
Applications: Detroit, Perkins

TS-1649 *Wet Clutch*
12V, CW, 10T-32mm Dia.,
4-Term. Solenoid
Replaces: 10461466, 10479617
Applications: Agco-White

TS-1695 *Wet Clutch*
12V, CW, 10T-40mm Dia.,
4-Term. Solenoid
Replaces: 10461475, 10479636
Applications: Agco-Allis

TS-1721 *Dry Clutch*
12V, CW, 10T-32mm Dia.,
w/ CE Grd. Stud, 4-Term. Sol.
Replaces: 10461474, 10479634
Applications: Cummins, Ford

TS-1760 *Dry Clutch*
24V, CW, 9T-36.5mm Dia.,
Replaces: 10479652
Applications: Trucks w/ MB Eng.

TS-1770 *Dry Clutch*
12V, CW, 10T-32mm Dia.,
Long B+ Solenoid Terminal
Replaces: 10461481, 10479642
Applications: Freightliner

01-10.07



PRODUCT NEWS

201_28M_TEX

“REMANUFACTURED” DELCO 28MT STARTER MOTORS

Cont'd



TS-1777 *Dry Clutch*
12V, CW, 10T-32mm Dia.,
4-Terminal Solenoid
Replaces: 10479640, 10479643
Applications: Cummins



TS-1625 *Dry Clutch*
12V, CW, 10T-32mm Dia.
Replaces: 10479615, 10479618
Applications: Cummins, Ford Truck



TS-1643 *Wet Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113293
Applications: Hyster, Perkins



S-8212 *Dry Clutch*
12V, CW, 10T-32mm Dia.
Replaces: 1113266, 1113295
Applications: Chevrolet, GMC



TS-1581 *Dry Clutch*
12V, CW, 9T-29.5mm Dia.
Replaces: 1113287, 10479619
Applications: Lincoln, Teledyne

TS-1633 *Wet Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113285, 10465349
Applications: Bobcat, Isuzu, Perkins



TS-1645 *Dry Clutch*
12V, CW, 10T-32mm Dia.
w/ Grd. Boss
Replaces: 10461471, 10479628
Applications: John Deere



TS-1731 *Dry Clutch*
24V, CW, 9T-36.5mm Dia.
Replaces: 10479626, 10479650
Applications: Freightliner, Sterling
w/ Mercedes Benz Eng.

TS-1584 *Dry Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113297, 10465057
Applications: Miller, Teledyne

TS-1660 *Wet Clutch*
24V, CW, 10T-32mm Dia.
Replaces: 10465405, 10479629
Applications: Cummins

TS-4063R *Wet Clutch*
24V, CW, 10T-40mm Dia.
Replaces: CA45F24-2, S115A24-1
Applications: Perkins



TS-1582 *Dry Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113289, 10465239
Applications: Mack, Renault



TS-1626 *Dry Clutch*
12V, CW, 10T-32mm Dia.
Replaces: 10465150, 10479614
Applications: Cummins, Ford Truck



S-8213 *Dry Clutch*
12V, CW, 10T-32mm Dia.
Replaces: 1113267, 1113296
Applications: Chevrolet, GMC



TS-1771 *Dry Clutch*
12V, CW, 9T-36.5mm Dia.,
No Auxiliary Magnetic Switch
Replaces: 10479645, 10479648
Applications: Trucks w/ MB Eng.



TS-1623 *Wet Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 10461484, 1113288
Applications: Clark, Perkins

TS-1648 *Dry Clutch*
12V, CW, 10T-40mm Dia.
Replaces: 1113284, 10461483
Applications: Cummins, Hough

TS-1639 *Dry Clutch*
24V, CW, 10T-32mm Dia.
Replaces: 10461453, 10479611
Applications: Chevrolet, GMC

S-8888 *Dry Clutch*
24V, CW, 11T-40.5mm Dia.
Replaces: S25-158,A,B; S25-160
Applications: Nissan F03